

ATTESTATION OF CONFORMITY

Issued to: Renac Power Technology Co., Ltd.
Block C-12, No. 20 Datong Road, Comprehensive Bonded Zone, Suzhou Hi-Tech District, 215151 Suzhou, Jiangsu, P.R. China

For the product: PV Grid-tied Inverter

Trade name: **RENAC**

Type/Model: R1-3.68K, R1-4K, R1-5K, R1-5K-A, R1-6K

Ratings: See Annex

Manufactured by: Renac Power Technology Co., Ltd.
Block C-12, No. 20 Datong Road, Comprehensive Bonded Zone, Suzhou Hi-Tech District, 215151 Suzhou, Jiangsu, P.R. China

Requirements: DIN VDE 0126-1-1 (VDE V 0126-1-1):2013-08

This Attestation is granted on account of an examination by DEKRA, the results of which are laid down in a confidential file no 6168191.51.

The examination has been carried out on one single specimen or several specimens of the product, submitted by the manufacturer. The Attestation does not include an assessment of the manufacturer's production. Conformity of his production with the specimen tested by DEKRA is not the responsibility of DEKRA.

Arnhem, 6 December 2023

Number: 6168191.02AOC

DEKRA Testing and Certification (Shanghai) Ltd.



Kreny Lin
Certification Manager

© Integral publication of this attestation and adjoining reports is allowed

Page 1 of 2

Document no. : 6168191.02AOC

Ratings of the test product:

Operating temperature range: - 25°C to + 60°C

Protective class: I

Ingress protection rating: IP65

Power factor range (adjustable): 0.8 leading...0.8 lagging

Over voltage category: III(AC), II(DC)

R1-3.68K:

PV input: Max. 600 Vdc, MPPT Voltage range 80~550 Vdc, rated MPP Voltage: 360 Vdc, max. 16 / 16 A, Isc 20 / 20 A

AC output: L/N/PE, 220 / 230 Vac, 50 / 60 Hz, max 16 A, rated power 3680 W, max. power 3680 VA

R1-4K:

PV input: Max. 600 Vdc, MPPT Voltage range 80~550 Vdc, rated MPP Voltage: 360 Vdc, max. 16 / 16 A, Isc 20 / 20 A

AC output: L/N/PE, 220 / 230 Vac, 50 / 60 Hz, max 20 A, rated power 4000 W, max. power 4400 VA

R1-5K:

PV input: Max. 600 Vdc, MPPT Voltage range 80~550 Vdc, rated MPP Voltage: 360 Vdc, max. 16 / 16 A, Isc 20 / 20 A

AC output: L/N/PE, 220 / 230 Vac, 50 / 60 Hz, max 25 A, rated power 5000 W, max. power 5500 VA

R1-5K-A:

PV input: Max. 600 Vdc, MPPT Voltage range 80~550 Vdc, rated MPP Voltage: 360 Vdc, max. 16 / 16 A, Isc 20 / 20 A

AC output: L/N/PE, 220 / 230 Vac, 50 / 60 Hz, max 21.7 A, rated power 5000 W, max. power 5000 VA

R1-6K:

PV input: Max. 600 Vdc, MPPT Voltage range 80~550 Vdc, rated MPP Voltage: 360 Vdc, max. 16 / 16 A, Isc 20 / 20 A

AC output: L/N/PE, 220 / 230 Vac, 50 / 60 Hz, max 27.3 A, rated power 6000 W, max. power 6000 VA

End