


On-Grid Inverters

R3 Navo Series

30kW / 36kW / 40kW / 50kW
Three Phase, 3 / 4 MPPTs



-  Compatible with 600W+ PV modules
-  150% DC input oversizing & 110% AC overloading
-  Remote firmware upgrade
-  Optional AFCI & Smart PID recovery function
-  Low start-up voltage at 200V
-  Type II SPD for both DC and AC

Model	R3-30K	R3-36K	R3-40K	R3-50K
PV Input				
Max. Recommended PV Power [Wp]	45000	54000	60000	75000
Max. PV Power for Single MPPT [Wp]	20000	20000	20000	20000
Max. PV Input Voltage [V]	1100			
MPPT Voltage Range [V]	180 – 1000			
Rated PV Input Voltage [V]	600			
Start-up Voltage [V]	200			
No. of MPP Trackers	3	3	4	4
No. of Input Strings per Tracker	2 / 2 / 2	2 / 2 / 2	2 / 2 / 2 / 2	2 / 2 / 2 / 2
Max. Input Current [A]	40 / 40 / 40	40 / 40 / 40	40 / 40 / 40 / 40	40 / 40 / 40 / 40
Max. Short-circuit Current [A]	50 / 50 / 50	50 / 50 / 50	50 / 50 / 50 / 50	50 / 50 / 50 / 50
AC Output				
Rated AC Output Power [W]	30000	36000	40000	50000
Max. AC Output Apparent Power [VA]	33000	39600	44000	55000
Max. AC Output Current [A]	50	60	66.6	83.3
Rated AC Voltage / Range [V]	3 / N / PE, 220 / 380, 230 / 400; ±20%			
Grid Frequency / Range [Hz]	50 / 60; ±5			
Adjustable Power Factor [cosφ]	0.8 leading – 0.8 lagging			
Output THDi (@Rated Output)	< 3%			
Efficiency				
Max. Efficiency	98.60%	98.70%	98.80%	98.80%
Euro Efficiency	97.80%	98.00%	98.00%	98.00%
Protection				
DC Switch	Integrated			
DC Insulation Monitoring	Integrated			
Input Reverse Polarity Protection	Integrated			
Anti-island Protection	Integrated			
Residual Current Monitoring	Integrated			
AC Overcurrent Protection	Integrated			
AC Short-circuit Protection	Integrated			
AFCI Protection	Optional			
PID Recovery Function	Optional			
DC Surge Protection	Integrated (Type II)			
AC Surge Protection	Integrated (Type II)			
General Data				
Dimensions (W * H * D) [mm]	585 * 480 * 220			
Weight [kg]	37			
Display	LED + OLED			
Communication	RS485, USB Upgrade, Optional: WiFi, 4G, Ethernet			
Ambient Temperature Range [°C]	-25 ~ +60			
Relative Humidity	0 ~ 100%			
Operating Altitude [m]	≤ 2000			
Night Self-consumption [W]	< 1			
Topology	Transformerless			
Cooling	Fan			
Ingress Protection	IP65			
Certifications & Standards				
Grid Regulation	NB/T 32004, ORDINANCE No.140, EN50549-1, EN50549-PL, EN50549-CZ, EN50549-GR, UNE217002/RD647, IEC61727/IEC62116, VDE0126, VDE4105			
Safety Regulation	EN 62919-1, EN 62619-2			
EMC	EN IEC 61000-6-1, EN IEC 61000-6-3, IEC 62920			